UNIVERSITY OF OXFORD

TRINITY TERM

CourseWork Module (CWM)

LEGO Football

Lab organizer: Prof. Kostas Margellos (kostas.margellos@eng.ox.ac.uk) Location: Control Laboratory, 5th Floor, Thom Building

April 28, 2022



Learning outcomes

The "LEGO Football" coursework module has four main objectives:

- 1. Apply in a more practical example tools from control theory and become familiar with the underlying concepts.
- 2. Provide an introduction to the entire control design process, that involves: physical modelling; design and analysis of a feedback control mechanism (stability and performance); model-based performance evaluation of the developed controller (in simulation); actual implementation using the systems' sensor-actuators (in hardware).
- 3. Become familiar with the use of MATLAB and Simulink for control design of systems with different characteristics: unstable, critically stable, stable.
- 4. Interact with robots and make them play football!

In these notes we consider a self-balancing, two-wheeled LEGO Mindstorms EV3 robot, and provide a companion for the laboratory tasks, providing details on the modelling and control design aspects. The robot is represented by a two-wheeled inverted pendulum, with the wheels being driven by DC motors. A nonlinear dynamical system governing its behaviour is derived based on the equations of motion for the wheels and the inverted pendulum, and on a simplified representation of the DC motor dynamics. The constructed model is then transformed to a linear dynamical system by means of linearization. Treating the DC motors' input voltage as control inputs, a Proportional-Integral (PI) controller is developed to ensure that the robot (two-wheeled inverted pendulum) can self-balance, a Proportional-Integral-Derivative (PID) controller is developed to allow forward/backward motion, and a Proportional (P) controller to allow turning.

Acknowledgements

These notes follow the notation and problem description of [1], [2], where some of the figures are also taken from (modified as appropriate), but the system dynamics are derived following an analysis similar to [3, 4]. We refer also to [5] for an alternative description and physical interpretation.

Robot assembling, hardware communication and the gamepad functionality is due to Dr. Izzi Mear (Teaching and Design Engineer, University of Oxford); the contribution of Dr. Filiberto Fele (University of Oxford) is also gratefully acknowledged. We are grateful to Dr. Coorous Mohtadi (MathWorks) for insightful discussions and input on the hardware implementation. The contribution of Dr. Luca Deori (Politecnico di Milano) in the first lab design involving LEGO Mindstorms NXT robots in Trinity Term 2015-16 is also gratefully acknowledged.

1 Physical description

Consider a two-wheeled LEGO Mindstorms EV3 robot, as shown in Figure 1, where both wheels are identical, and are driven by identical motors. The main brick is responsible for any communication and processing when interacting with MATLAB/Simulink. Our configuration is equipped with two sensors: a gyro sensor that as will be discussed in the sequel contains information on the robot's angular displacement from the vertical axis, and a touch sensor that will be used to reset the motors. Actuation inputs to the robot constitute the voltages applied to the left and right motor, respectively.

From a mathematical point of view we can represent the robot by a two-wheeled inverted pendulum (see Figure 2), whose side and top view are shown in Figure 3. It can be thought of as a combination of a unicycle-like model and an inverted pendulum.



Figure 1: LEGO Mindstorms EV3 robot.

Variable θ denotes the wheels' angle, ψ denotes the pitch angle of the pendulum, and ϕ the yaw angle of the robot. Before providing the equations of motion of the two-wheeled inverted pendulum, it would be convenient to establish certain relations between the cartesian coordinates (x_w, y_w, z_w) of the center of each wheel $w \in \{l, r\}$, where l, r, indicate the left and right wheel, respectively, the coordinates of the middle point (x_m, y_m, z_m) along the wheel axis, and the ones of the middle point (x_b, y_b, z_b) of the upper body, as a function of the angles θ , ψ and ϕ .

To this end, consider the reference coordinate frame of Figure 3, and denote by

$$\theta = \frac{1}{2}(\theta_r + \theta_l),\tag{1}$$

the average angle of the right and left wheel, respectively. The rate of change of the yaw angle $\dot{\phi}$ can be written as a function of $\dot{\theta}_r$ and $\dot{\theta}_l$ given by

$$\dot{\phi} = \frac{R}{W} (\dot{\theta}_r - \dot{\theta}_l). \tag{2}$$



Figure 2: Inverted pendulum representation of the LEGO Mindstorms EV3 robot.



Figure 3: Side and top view of the two-wheeled inverted pendulum.

To see this notice that by the left panel of Figure 4 we have that the arc length travelled by wheel w for an angular displacement $d\theta_w$, incurred within some time interval dt, is equal to $R\theta_w$, $w \in \{l, r\}$. Consider now the right panel of Figure 4, where x - y denotes the reference coordinate frame of Figure 3. We then have that for dt (and hence also for $d\phi$) small enough, $d\phi \approx \tan d\phi = \frac{Rd\theta_l - Rd\theta_r}{W}$. However, since an increase by $d\phi$ tends to decrease ϕ according to the convention of Figure 4, we have that

$$\dot{\phi} = -\lim_{dt\to 0} \frac{d\phi}{dt} = -\frac{R}{W} (\dot{\theta}_l - \dot{\theta}_r), \tag{3}$$

which leads to (2). The notation $\frac{d\phi}{dt}$ should not be confused with the time-derivative of ϕ , which is in turn denoted by $\dot{\phi}$, but is the ratio between $d\phi$ and dt. By (2) it follows that the yaw motion requires a differential voltage input.



Figure 4: Left panel: Wheel's side view for an angular displacement $d\theta_w$, $w \in \{l, r\}$. Right panel: Top view of the robot's displacement during a right turn.

We have that

$$(x_m, y_m, z_m) = \left(\int \dot{x}_m dt, \int \dot{y}_m dt, R\right),\tag{4}$$

where

$$(\dot{x}_m, \dot{y}_m) = (R\dot{\theta}\cos\phi, R\dot{\theta}\sin\phi).$$
(5)

Note that \dot{x}_m, \dot{y}_m , correspond to the projection of the velocity vector $R\dot{\theta}$ on the x and y axis, respectively.

Q1. Calculate the coordinates (x_l, y_l, z_l) and (x_r, y_r, z_r) of the left and right wheel, respectively, and the coordinates of the middle point of the upper body, as a function of x_m, y_m, z_m and ϕ .

For each $w \in \{l, r\}$, let $F_{s,w}$ denote the static friction force due to the contact between wheel wand the ground, whereas let $F_{h,w}$ denote the reaction force due to the friction caused by the contact between the wheel and the main body. Denote also by $F_{p,w}$ the vertical force due to the contact between each wheel and the main body. Let T_w denote the torque causing rotation of wheel w, produced by the associated DC motor, and by $T_{f,w}$ the component of the friction torque due to the contact between the DC motor and the main body with direction opposite to that of T_w .

Q2. Provide free body diagrams for each of the wheels and the pendulum.

Each wheel $w, w \in \{l, r\}$, is driven by a DC motor. The behaviour of the DC motor is captured by the electric circuit of Figure 5, where R_{dc} and L_{dc} denote the resistance and inductance, respectively, of the armature circuit, which is assumed to be the same for both motors. When the armature circuit is placed within a fixed, separately excited field, torque causing rotation is generated. Variable u_w denotes the voltage input, which serves as a control variable for our purposes, I_w denotes the flowing current, and $u_{e,w}$ denotes the induced voltage, referred to as back electromotive force (back EMF), which is proportional to the angular velocity of the motor at wheel w, with proportionality constant K_e .



Figure 5: Electric circuit describing the behavior of the DC motor at wheel $w, w \in \{l, r\}$. Torque is generated when the armature circuit is placed within a fixed, separately excited field.

Q3. Assume that there are no current transients, and let

$$u_1 = \frac{1}{2}(u_l + u_r), \ u_2 = \frac{1}{2}(u_l - u_r).$$
 (6)

Show that

$$(T_l + T_r) - (T_{f,l} + T_{f,r}) = 2\frac{K_T}{R_{dc}}u_1 - 2\left(\frac{K_T K_e}{R_{dc}} + b\right)(\dot{\theta} - \dot{\psi}),\tag{7}$$

$$(T_r - T_l) - (T_{f,r} - T_{f,l}) = -2\frac{K_T}{R_{dc}}u_2 - \frac{W}{R}\Big(\frac{K_T K_e}{R_{dc}} + b\Big)\dot{\phi}.$$
(8)

Hint: For each $w \in \{l, r\}$, work according to the following steps:

- 1. Provide an expression for the back EMF $u_{e,w}$;
- 2. Write I_w as a function of u_w , $\dot{\theta}_w$ and $\dot{\psi}$;
- 3. Use the fact that T_w is proportional to the armature current I_w , i.e., $T_w = K_T I_w$;
- 4. Model $T_{f,w}$ as a damper, using the friction coefficient b in Table 1, Appendix A.

2 Mathematical modelling

We will first design a controller that allows the robot to self-balance and move forward/backward, and, at a next stage, we will focus on the yaw motion. To achieve this and decouple the yaw motion we assume that $\phi = 0$, i.e., the robot's heading is aligned with the x axis, when deriving the equations of motion for the wheels and the pendulum. This analysis is approximate, but accurate enough from a control point of view, leading to the same linearized dynamical system.

Definitions for all other parameters, treated as constants in our analysis, and their numerical values, are taken from [1], and can be found in Table 1, in Appendix A.

2.1 Self-balance and forward/backward motion

Q 4. For each $w = \{r, l\}$, derive the equations of motion for the wheel w due to its horizontal and its rotational motion. Show that they can be combined to form

$$(2mR^2 + 2J)\ddot{\theta} = (T_l + T_r) - (T_{f,l} + T_{f,r}) - (F_{h,l} + F_{h,r})R - 2\bar{b}\dot{\theta}.$$
(9)

Hint: To obtain (9), work according to the following steps:

- 1. Consider the cartesian motion. Under the assumption $\phi = 0$, obtain an expression for \ddot{x}_w , which denotes the wheel's linear acceleration along the x axis.
- 2. Consider the rotational motion. Obtain an expression for θ_w , which denotes the wheel's angular acceleration. Except from $T_{f,w}$, the friction torque due to rotation along the wheel axis needs to be taken into account as well. To model this, use \bar{b} from Table 1, in Appendix A.
- 3. Express \ddot{x}_w as a function of $\ddot{\theta}_w$ using (5), and use (1) to obtain (9).

Q5. Derive the equations of motion for the pendulum, considering both its horizontal motion and its rotation along the pitch angle direction. Show that they are given by

$$M(R\ddot{\theta} + L\cos\psi\ddot{\psi} - L\sin\psi\dot{\psi}^2) = (F_{h,l} + F_{h,r}),\tag{10}$$

$$M(-L\sin\psi\ddot{\psi} - L\cos\psi\dot{\psi}^{2}) = (F_{p,l} + F_{p,r}) - Mg,$$
(11)

$$J_{\psi}\ddot{\psi} = (T_{f,l} + T_{f,r}) - (T_l + T_r) + (F_{p,l} + F_{p,r})L\sin\psi - (F_{h,l} + F_{h,r})L\cos\psi.$$
(12)

Hint: To obtain (10) - (12), work according to the following steps:

- 1. Consider the cartesian motion. The pendulum is moving both in the horizontal direction (only along the x axis since $\phi = 0$) and along the vertical direction. Hence, obtain an expression for \ddot{x}_b and \ddot{z}_b , which denote the linear acceleration of the middle point of the main body along the x axis and z axis, respectively.
- 2. Express \ddot{x}_b and \ddot{z}_b as a function of θ , ψ and their derivatives using (5) and (??). This leads to (10) and (11).
- 3. Consider the rotational motion. Obtain an expression for $\ddot{\psi}$, which denotes the angular acceleration along the pitch direction, thus leading to (12).

Q 6. Combine (9), (10), (11), and (12), by eliminating unknown force vectors, and show that the nonlinear equations of motion that govern the robot's self-balance and forward/backward motion take the form

$$MLR\cos\psi\ddot{\theta} + (ML^2 + J_{\psi})\ddot{\psi} - MgL\sin\psi = -(T_l + T_r) + (T_{f,l} + T_{f,r}),$$
(13)

$$(2mR^2 + 2J + MR^2)\ddot{\theta} + MLR\cos\psi\ddot{\psi} - MLR\sin\psi\dot{\psi}^2 = (T_l + T_r) - (T_{f,l} + T_{f,r}) - 2\bar{b}\dot{\theta}.$$
 (14)

Q7. Let $x_1 = [\theta \ \psi \ \dot{\theta} \ \dot{\psi}]^\top \in \mathbb{R}^4$. Using linearization around $x_1^* = [0 \ 0 \ 0 \ 0]$ and $u_1^* = 0$ (recall the definition of u_1 in (6)), show that the equations that govern the robot's behaviour (13) and (14), can be written in state space form as

$$\dot{x}_1 = A_1 x_1 + B_1 u_1, \tag{15}$$

$$y = C_1 x_1 + D_1 u_1, (16)$$

where

$$A_{1} = \begin{bmatrix} 0 & 0 & 1 & 0 \\ 0 & 0 & 1 \\ 0 & -gRM^{2}L^{2}\frac{1}{q} & -2(MRL + ML^{2} + J_{\psi})(\frac{K_{T}K_{e}}{R_{dc}} + b)\frac{1}{q} - 2(ML^{2} + J_{\psi})\overline{b}\frac{1}{q} & 2(MRL + ML^{2} + J_{\psi})(\frac{K_{T}K_{e}}{R_{dc}} + b)\frac{1}{q} \\ 0 & gML((2m + M)R^{2} + 2J)\frac{1}{q} & 2((2m + M)R^{2} + 2J + MRL)(\frac{K_{T}K_{e}}{R_{dc}} + b)\frac{1}{q} + 2MRL\overline{b}\frac{1}{q} & -2((2m + M)R^{2} + 2J + MRL)(\frac{K_{T}K_{e}}{R_{dc}} + b)\frac{1}{q} \end{bmatrix}$$

$$B_{1} = \begin{bmatrix} 0 \\ 0 \\ 2(MRL + ML^{2} + J_{\psi})\frac{K_{T}}{R_{dc}}\frac{1}{q} \\ -2((2m+M)R^{2} + 2J + MRL)\frac{K_{T}}{R_{dc}}\frac{1}{q} \end{bmatrix}, C_{1} = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}, D_{1} = \begin{bmatrix} 0 \\ 0 \end{bmatrix},$$

and $q = ((2m+M)R^2 + 2J)(ML^2 + J_{\psi}) - M^2R^2L^2$.

Note that the output corresponds to θ and $\dot{\psi}$. In practice, $\dot{\psi}$ is directly available via the gyro sensor, whereas θ can be calculated by means of the DC motor angle measurement $\theta - \psi$, where ψ is calculated from $\dot{\psi}$ by means of numerical integration.

2.2 Yaw motion

Notice that the sum of the motors' voltages $u_l + u_r$ is responsible for the forward/backward motion of the robot. As suggested by **Q3**, the yaw motion emanates from a differential voltage, i.e., $u_l - u_r$. Setting $x_2 = [\phi \ \dot{\phi}]^\top \in \mathbb{R}^2$, the yaw dynamics linearized around $x_2^* = [0 \ 0]^\top$, $u_2^* = 0$ are given by the state space form

$$\dot{x}_2 = A_2 x_2 + B_2 u_2,\tag{17}$$

$$y = C_2 x_2 + D_2 u_2, (18)$$

where

$$A_{2} = \begin{bmatrix} 0 & 1 \\ 0 & -\frac{W^{2}}{2R^{2}} \left(\frac{K_{T}K_{e}}{R_{dc}} + b + \bar{b}\right) \frac{1}{\frac{1}{2}mW^{2} + J_{\phi} + \frac{JW^{2}}{2R^{2}}} \end{bmatrix}, B_{2} = \begin{bmatrix} 0 & 0 \\ -\frac{W}{R}\frac{K_{T}}{R_{dc}}\frac{1}{\frac{1}{2}mW^{2} + J_{\phi} + \frac{JW^{2}}{2R^{2}}} \end{bmatrix}, C_{2} = \begin{bmatrix} 1 & 0 \end{bmatrix}, D_{2} = 0.$$

Note that we have assumed that the yaw angle ϕ can be measured directly.

2.3 Modeling in MATLAB Simulink

Go to the LEGO_SW folder in your directory. Two files are needed for this task: the run_LEGO_SW.m MATLAB file, where all parameters shall be defined, and the Simulink file LEGO_SW.slx. The overall Simulink architecture exhibits the form of Figure 6, where the Signal Builder blocks provide the means to design reference trajectories for $\dot{\theta}^{\text{ref}}$ and $\dot{\phi}^{\text{ref}}$.

Q8. Define values for all necessary parameters according to Table 1, Appendix A, in run_LEGO_SW.m. Use the Simulink Library Browser to fill in the subsystem robot of LEGO_SW.slx shown in Figure 6.

Hint: Check the State-Space block as a modelling option from the Simulink Library Browser.



Figure 6: Simulink architecture of LEGO_SW.slx.

3 Control design – Self-balancing and forward/backward motion

We aim at designing u_1 for the two-wheeled inverted pendulum to self-balance, and track some reference signal $x_1^{\text{ref}} = [\theta^{\text{ref}} \psi^{\text{ref}} \dot{\theta}^{\text{ref}}]^{\top}$, such that $\psi^{\text{ref}} = \dot{\psi}^{\text{ref}} = 0$, i.e., the robot should move forward/backward with the pendulum balancing along the vertical position. Notice that, since it can be shown that x_1^* is an unstable equilibrium of (15), even when $x_1^{\text{ref}} = x_1^*$ and the robot is not moving, a controller is needed to stabilize the system at x_1^* , and the pendulum to self-balance. To achieve this task we consider the feedback control structure of Figure 7.

Recall that the output y includes the states θ and $\dot{\psi}$. We employ a Proportional-Integral (PI) controller and a Proportional-Integral-Derivative (PID) controller to regulate $\dot{\psi}$ and θ , to their reference values, respectively. Notice that the PI controller for $\dot{\psi}^{\text{ref}} - \dot{\psi}$ is effectively a proportional controller assuming feedback of the states ψ , $\dot{\psi}$, with gains $K^{I}_{\dot{\psi}}$, $K^{P}_{\dot{\psi}}$, respectively, and the state ψ being reconstructed from $\dot{\psi}$ via numerical integration. Similarly, the PID controller could be thought of as the composition of a PI controller concerning $\theta^{\text{ref}} - \theta$, with a proportional controller with gain K^{D}_{θ} for $\dot{\theta}^{\text{ref}} - \dot{\theta}$, with the latter being constructed via numerical differentiation from $\theta^{\text{ref}} - \theta$.

3.1 Self-balancing pitch PI controller

Consider the system of Figure 7. We start by designing the inner, PI controller so that the robot can self-balance. To this end, we aim at choosing the feedback gains $K_{\dot{\psi}}^P$, $K_{\dot{\psi}}^I$ that are related to the pendulum's pitch angle so that the unstable system becomes stable.

Q 9. Using MATLAB, determine the system's transfer function (matrix) G(s) from $u_1 \to y$. Denote by G_{θ} and $G_{\dot{\psi}}$ the transfer functions from $u_1 \to \theta$ and from $u_1 \to \dot{\psi}$, respectively. Is the system stable?

Hint: Check MATLAB commands ss and zpk.



Figure 7: Feedback control structure.

The transfer function of the PI controller is given by $G_{\rm PI}(s) = K_{\dot{\psi}}^P + \frac{K_{\dot{\psi}}^I}{s} = K_{\dot{\psi}}^P \left(\frac{s + K_{\dot{\psi}}^I/K_{\dot{\psi}}^P}{s}\right)$. Since $\dot{\psi}^{\rm ref} = 0$, consider the inner loop (blue dashed box) of Figure 7.

Q10. Using MATLAB, choose the gains $K^P_{\dot\psi}, \, K^I_{\dot\psi}$ of the PI pitch controller.

- 1. Place first the zero $z_{\mathbf{PI}} = K^I_{\dot{\psi}}/K^P_{\dot{\psi}}$ of the controller on the left of the negative pole of $G_{\dot{\psi}}$ that is closest to the origin.
- 2. Determine the gain $K_{\dot{\psi}}^P$ by checking the root locus of the open-loop transfer function $G_{\dot{\psi}} \frac{s+K_{\dot{\psi}}^I/K_{\dot{\psi}}^P}{s}$. Plot the negation of this function since MATLAB allows only for positive gains in root locus.

Hint: Check MATLAB commands tf and rlocus. Ensure to negate the selected gains since the root locus of the negation of the transfer function was considered.

Q11. Determine the transfer function $\widetilde{G}(s)$ of the inner loop system of Figure 7. Is the corresponding system stable?

Hint: Check MATLAB command minreal, and use the equivalence between the system's state space representation and the associated transfer functions computed in Q9 as shown in Figure 8.



Figure 8: State space representation of the plant appearing in Figure 7 and the associated transfer functions.

3.2 Forward/backward motion PID controller

By inspection of $\widetilde{G}(s)$ it should be observed that there is one pole at the origin. As a result, the system will be unstable after a step input. We will thus design a PID controller to ensure a stable closed-loop performance. Moreover, $\widetilde{G}(s)$ exhibits one (odd number) of right-half plane zeros and is strictly proper; we thus anticipate an initial undershoot in the system's response after a step reference increase. Note that the presence of a right-half plane zero imposes limitations on the cross-over frequency, and hence the bandwidth. In particular, the "slower" the right-half plane zero, the lower the cross-over frequency is expected to be (see Chapter 11.7 in [6]).

Control design problem: Consider the following stability and performance specifications:

- 1. Phase margin PM greater than 50° .
- 2. Step response settling time T_s less than 10s.

The transfer function of the PID controller is given by

$$G_{\rm PID}(s) = K_{\theta}^{P} + \frac{K_{\theta}^{I}}{s} + K_{\theta}^{D}s = K_{\theta}^{D} \frac{s^{2} + (K_{\theta}^{P}/K_{\theta}^{D})s + (K_{\theta}^{I}/K_{\theta}^{D})}{s}.$$
 (19)

Q12. Using MATLAB, choose the gains K^P_{θ} , K^I_{θ} and K^D_{θ} of the PID controller.

- 1. Turn the control design specifications into requirements for the damping ratio ζ and the natural frequency ω_n .
- 2. Place the zeros of the PID controller in the desired $\zeta \omega_n$ region, by determining
- r have one to be the relation of the relation of the desired ζ w_n region, sy determining r_{PD} = K_θ^P/K_θ^D and r_{ID} = K_θ^I/K_θ^D.
 3. Determine the range of admissible K_θ^D values by the root locus of the open loop transfer function size function (s²+(K_θ^P/K_θ^D)s+(K_θ^I/K_θ^D)/s) G̃(s) (so that the closed loop system is stable). Plot the negation of this function since MATLAB allows only for positive gains in root locus.
- 4. Choose the gain K^D_{θ} in this range, ensuring (from the root locus) that the closed loop system will operate in the desired $\zeta - \omega_n$ region. Verify by the Bode plot that the desired phase margin specification is satisfied. Hint: Check MATLAB command margin.

Ensure to negate the selected gains since the root locus of the negation of the transfer function was considered.

- 1. Calculate the transfer function of the closed loop system, i.e., from $\theta^{\text{ref}} \rightarrow \theta$ Q13. with reference to Figure 7.
 - 2. Verify the settling time specification by simulating a unit step response of the closed loop system.

Hint: Check MATLAB command step.

Q 14. Comment on the stability of the closed loop system by drawing the Nyquist diagram in MATLAB.

Hint: Check MATLAB command nyquist.

For a similar PID design procedure we also refer to [7] (Example 9.10, Chapter 9).

3.3Modelling in MATLAB Simulink

Go to the run_LEGO_SW.m MATLAB file, define values for the control gains as calculated in the aforementioned tasks, and recall the general architecture as shown in Figure 6.

Q15. Use the Simulink Library Browser to fill in subsystems reference, controller dot_psi, controller theta and robot input of LEGO_SW.slx shown in Figure 6.

4 Control design – Yaw motion

4.1 Yaw motion

We consider now the task of designing u_2 , which governs the yaw motion of the two-wheeled inverted pendulum. By inspection of A_2 , B_2 , it can be observed that (17) corresponds to a stable dynamical system (it has negative real eigenvalues). In particular, it is in controllable canonical form (see Chapter 9 in [8]), hence the choice of gains for a state feedback controller via pole placement is anticipated to be straightforward. For this particular structure, however, applying a constant input u_2 is sufficient for stabilizing the second component $\dot{\phi}$ of x_2 to some desired reference value $\dot{\phi}^{\text{ref}}$ (we assume that $\ddot{\phi}^{\text{ref}} = 0$); using a state feedback we could also enforce the desired stabilization rate.

To see this, denote by $A_2^{(2,2)}$, $B_2^{(2)}$ the corresponding elements of A_2 and B_2 , respectively. Let

$$u_2 = -\frac{A_2^{(2,2)}}{B_2^{(2)}} \dot{\phi}^{\text{ref}}.$$
(20)

By (20), (17), we then have that

$$(\ddot{\phi} - \ddot{\phi}^{\text{ref}}) = A_2^{(2,2)}(\dot{\phi} - \dot{\phi}^{\text{ref}}).$$
 (21)

Notice that $A_2^{(2,2)} < 0$, hence we can stabilize $\dot{\phi}$ to $\dot{\phi}^{\text{ref}}$, and as a result ϕ to ϕ^{ref} , where the latter is the integral of $\dot{\phi}^{\text{ref}}$.

Q 16. Is (20) an open or a closed loop control design? What would you expect if controller (20) is applied to the LEGO Mindstorms EV3 robot?



Figure 9: Feedback control for yaw motion.

Consider the block diagram structure of Figure 9. A Proportional (P) controller with gain K_{ϕ}^{P} is employed now to regulate ϕ to ϕ^{ref} .

Q17. Consider the matrices C_2 and D_2 defined in Section 2.2, and choose the gain K_{ϕ}^P of the proportional yaw controller. This can be done via simulation to ensure that the closed loop system is stable and sufficiently fast.

4.2 Modelling in MATLAB Simulink

Go to the run_LEGO_SW.m MATLAB file, define values for the gains associated with the yaw controller as calculated in the aforementioned tasks, and recall the general architecture as shown in Figure 6.

Q 18. Use the Simulink Library Browser to fill in subsystem controller yaw of LEGO_SW.slx shown in Figure 6. Consider two separate cases according to whether (20) or the proportional controller of Q17 is employed.

5 Control deployment

5.1 Simulation in MATLAB Simulink

Go to the LEGO_SW folder in your directory, and consider the run_LEGO_SW.m MATLAB file, and the Simulink file LEGO_SW.slx. With reference to Figure 6, all subsystems should be now filled in and connected.

Ensure that all parameters and control gains needed in the Simulink file are defined in the file run_LEGO_SW.m, and run both files.

Q 19. Plot the time evolution of the states x_1 and x_2 of the robot to investigate its performance in terms of tracking reference signals. Use the Signal Builder block of the Simulink Library Browser to construct reference signals that involve both positive and negative step changes.

Q20. Plot in separate graphs the trajectory traversed by the wheel's middle point x_m and y_m , respectively, as a function of time.

5.2 Simulation on LEGO Mindstorms EV3

Go to the LEGO_HW folder in your directory. Two files are needed for this task: the run_LEGO_HW.m MATLAB file, where all parameters shall be defined, and the Simulink file LEGO_HW.slx. Switch on the LEGO Mindstorms EV3 on by pressing the EV3 main Button. The EV3 intelligent brick should blink and turn green. From the brick buttons navigate to Settings and confirm that EV3 is connected to WiFi and hence can communicate with the desktop computer.

The Simulink architecture exhibits the same form with that of Figure 6, with the difference that the controllers are now implemented in discrete time, and the state space representation of the robot should now be replaced by LEGO Mindstorms EV3 blocks from the relevant Simulink library.

To this end, follow the subsequent steps:

- 1. Go to the robot subsystem, and then enter in the EV3 $\,$ Robot subsystem that can be found therein.
- 2. Open the Simulink Support Package for LEGO MINDSTORMS EVE3 Hardware that can be found in the Simulink Library Browser. You should find a list of blocks as shown in Figure 10.
- 3. Drag and drop from this list to the EV3 Robot, two Motor, two Encoder and one Gyro Sensor blocks.
- 4. Connect to the Motor blocks the outputs of the robot input subsystem, and use the Encoder and the Gyro Sensor to obtain sensor measurements for the angle of the left and right motors, and the gyro output, respectively.
- 5. Connect all sensor signals to a Bus Creator block selected from the Simulink Library Browser. The output of this bus constitutes the Raw Sensors output of the EV3 Robot subsystem.

Ensure that the EV3 brick input port appearing in the Gyro Sensor block corresponds to the port where the gyro sensor is connected in the robot. Moreover, since we have a discrete time implementation, ensure that in all blocks the sample time is set to T_s (its numerical value is

provided in the run_LEGO_HW.m). As an example see Figure 11, while the same comments apply for the other blocks. Moreover, the name of the signals appearing in the Bus Creator block should be in correspondence with the ones appearing in the Bus Selector block in the Sensor Processing subsystem.

Once the EV3 Robot subsystem is filled in, define the control gain values calculated in Sections 3 and 4 in run_LEGO_HW.m, and run the file. Ensure that all parameters needed in the Simulink file are defined in run_LEGO_HW.m. Then run LEGO_HW.slx following the procedure outlined in LEGO_Football_guidelines_to_connect.pdf, making sure that your robot can communicate with MATLAB/Simulink via Wi-Fi.



Figure 10: Simulink library related to the support package for LEGO Mindstorms EV3 hardware.

| $\bullet \circ \circ$ | Block Parameters: Gyro Sensor1 | | | | |
|---|--------------------------------------|-------|--|--|--|
| LEGO MINDSTORMS EV3 Gyro Sensor (mask) (link) | | | | | |
| Measure the rat | e of rotation in degrees per second. | | | | |
| Select the EV3 brick input port that is connected to this sensor. | | | | | |
| Parameters | | | | | |
| EV3 brick input | port: 1 | | | | |
| Sample time: | | | | | |
| Ts | | : | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | OK Cancel Help | Apply | | | |

Figure 11: Gyro Sensor block.

Q 21. Plot the time evolution of the states x_1 and x_2 of the robot to investigate its performance in terms of tracking the reference signals.

Q 22. Compare reference tracking when using the yaw controller of (20) versus the proportional controller of Q17. What do you observe compared to your answer in Q18?

Q23. Determine appropriate reference trajectories and show that your robot can track the penalty area perimeter.

5.3 Driving the robot via a gamepad

Go to the LEGO_HW_game folder in your directory. Two files are needed for this task: the run_LEGO_HW.m MATLAB file as updated at the end of Section 5.2, where all parameters shall be defined, and the new Simulink file LEGO_HW_game.slx.

This Simulink file has the same architecture with LEGO_HW.slx, with the addition that it includes a *reset* and a *gamepad* functionality to facilitate the task of playing football. If the robot falls or crashes with other robots simply press the Touch Sensor (red button) on the EV3 instead of rerunning the MATLAB script; it resets the integrators and stops the motors. Run run_LEGO_HW.m (all parameters needed in the Simulink file should have been defined therein), as well as the gamepad Simulink file run_gamepad.slx (see LEGO_Football_guidelines_to_connect.pdf for guidelines on edits needed in this file). Once this is running, then run LEGO_HW_game.slx making sure that the gains of the controllers have been updated according to the the ones that you have defined in the m-file.

Q24. Repeat Q23 and drive your robot around using the gamepad. Use an additional motor so that your robot can kick/pass the ball.

Your robot should be ready to play football! The overall set-up should look like the one of Figures 12 and 13.



Figure 12: Place your robot on the football rug and start playing football!



Figure 13: Laboratory set-up with 6 Mindstorms EV3 robots.

6 Control design via pole placement

We consider an alternative control design technique. To this end, consider the architecture of Figure 7. Set $z = \int (\theta - \theta^{\text{ref}}) dt$, thus leading to $\dot{z} = \theta - \theta^{\text{ref}}$. Let $K = \begin{bmatrix} K_{\theta}^{P} & K_{\psi}^{I} & K_{\theta}^{D} & K_{\psi}^{P} & K_{\theta}^{I} \end{bmatrix}^{\top} \in \mathbb{R}^{5}$, and denote by \bar{C}_{1} the first row of C_{1} . By inspection of Figure 7, we then have that

$$u_1 = -K \begin{bmatrix} x_1 \\ z \end{bmatrix} + K \begin{bmatrix} x_1^{\text{ref}} \\ 0 \end{bmatrix}.$$
 (22)

By (15) and (22), we have for the closed-loop system that

$$\begin{bmatrix} \dot{x}_1 \\ \dot{z} \end{bmatrix} = \left(\begin{bmatrix} A_1 & 0_{4\times 1} \\ \bar{C}_1 & 0 \end{bmatrix} - \begin{bmatrix} B_1 \\ 0 \end{bmatrix} K \right) \begin{bmatrix} x_1 \\ z \end{bmatrix} + \begin{bmatrix} B_1 K \\ [-\bar{C}_1 & 0] \end{bmatrix} \begin{bmatrix} x_1^{\text{ref}} \\ 0 \end{bmatrix}.$$
(23)

Note that he open-loop system is unstable, since A_1 has one eigenvalue with positive real part. We can determine K by placing the poles (eigenvalues) of $\begin{pmatrix} A_1 & 0_{4\times 1} \\ \bar{C}_1 & 0 \end{bmatrix} - \begin{bmatrix} B_1 \\ 0 \end{bmatrix} K$ at some targetlocation $p = [p_1 \ p_2 \ p_3 \ p_4 \ p_5]$, so that the closed-loop system is stable (all elements of p should have negative real parts). This can be achieved by means of the so called *pole placement* procedure.

Pole placement procedure:

- 1. Compute the target characteristic polynomial (whose roots are p_1, \ldots, p_5). This is given by $\prod_{i=1}^5 (s-p_i)$.
- 2. Compute the characteristic polynomial associated with the closed loop system whose state space matrix is given by $\left(\begin{bmatrix} A_1 & 0_{4\times 1} \\ \overline{C}_1 & 0 \end{bmatrix} \begin{bmatrix} B_1 \\ 0 \end{bmatrix} K\right)$. This is given by

$$\det\left(sI - \left(\begin{bmatrix} A_1 & 0_{4\times 1} \\ \bar{C}_1 & 0 \end{bmatrix} - \begin{bmatrix} B_1 \\ 0 \end{bmatrix} K \right) \right).$$

3. Equate the coefficients of the two characteristic polynomials. Notice that the coefficients of the one of step 2 depend on the gains in K that need to be determined.

Note that the characteristic polynomial of a given matrix A is given by the determinant det(sI - A), which is in turn the denominator of the system's transfer function, and when equating it with zero, its roots correspond to the poles of the system. I denotes an identity matrix of appropriate dimension. The aforementioned procedure results in solving a system of 5 equations (since the characteristic polynomials are of 5-th order), linear in the gains in K. For more details the reader is referred to [8] (Chapter 9). However, this can be achieved using MATLAB.

Q 25. Choose p so that a complex pole pair is dominant, meeting the control design specifications of Section 3.2. Calculate the control gain vector K that ensures that the poles of the closed-loop system are in the locations contained in p. Hint: Check the MATLAB command place.

Q26. Compare the performance of the set of gains calculated via pole placement with those calculated via root locus and bode plots. Perform any fine tuning if appropriate.

Q 27. Consider the Simulink architecture of $LEGO_SW.slx$, as illustrated in Figure 6. Simplify the model to include only two state space Simulink blocks and two state feedback control loops, with the one feedback gain being the vector K.

The overall laboratory set-up is in the form of Figure 14. Each robot is still automatically stabilized via the developed control scheme, but is driven manually by setting the reference values $\dot{\theta}^{\text{ref}}$ and $\dot{\phi}^{\text{ref}}$ in real-time via the gamepad according to Figure 14.



Figure 14: Real-time steering principle, where $\dot{\psi}$ control refers the the PI controller regulating the pitch angle to zero, θ control refers to the PID controller regulating the forward/backward motion of the EV3, and ϕ control refers to the P controller regulating the yaw motion.

Q28. How many feedback control loops do you recognize in Figure 14?

Appendix A

| Symbol | Value | Measurement units | Physical meaning |
|------------|-----------------------------|-------------------|--|
| g | 9.81 | m/s^2 | gravity acceleration |
| m | 0.024 | kg | wheel's mass |
| M | 0.6 | kg | main body's mass |
| R | 0.027 | m | wheel's radius |
| D | 0.04 | $\mid m$ | main body's depth |
| W | 0.14 | $\mid m$ | main body's width |
| H | 0.22 | $\mid m$ | main body's length |
| L | $\frac{H}{2}$ | | main body's half-length |
| J | $\frac{\overline{mR^2}}{2}$ | kgm^2 | wheel's moment of inertia |
| J_{ψ} | $\frac{ML^2}{3}$ | kgm^2 | pitch moment of inertia |
| J_{ϕ} | $\frac{M(W^2+D^2)}{12}$ | kgm^2 | yaw moment of inertia |
| J_{dc} | $1e^{-5^{12}}$ | kgm^2 | DC motor's moment of inertia |
| R_{dc} | 6.69 | Ω | DC motor's resistance |
| K_e | 0.468 | Vs/rad | back EMF constant |
| K_T | 0.317 | Nm/A | DC motor's torque constant |
| $\mid b$ | 0.0022 | Nms/rad | friction coefficient between main body |
| | | | and DC motor |
| $ \bar{b}$ | 0.0022 | Nms/rad | friction coefficient due to rotation along |
| | | | the wheel axis |

Table 1: Parameters and numerical values.

References

- Y. Yamamoto, "NXTway-GS Model-Based Design Control of Self-balancing twowheeled robot build with LEGO Mindstorms NXT," *Technical Report*, pp. 1–73, 2009.
 [Online]. Available: http://www.mathworks.com/matlabcentral/fileexchange/19147-nxtwaygs-self-balancing-two-wheeled-robot-controller-design
- [2] "Simulink and LEGO MINDSTORMS NXT," Technical Report, MathWorks, Inc., pp. 1–23, 2013.
- [3] Y. Kim, S. Kim, and Y. Kwack, "Dynamic analysis of a non-holonomic two-wheeled inverted pendulum robot," *Journal of Intelligent and Robotic Systems*, vol. 44, no. 1, pp. 25–46, 2005.
- [4] B. Bonafilia, N. Gustafsson, P. Nyman, and S. Nilsson, "Self-balancing two-wheeled robot," *Technical Report, Chalmers University of Technology*, pp. 1–11, 2013. [Online]. Available: http://sebastiannilsson.com/wp-content/uploads/2013/05/Self-balancing-two-wheeledrobot-report.pdf
- [5] "NXT SegWay Robot, Lesson 1," Technical Report, SolidWorks, pp. 1–45, 2013.
- [6] K. Astrom and R. Murray, "Feedback Systems An Introduction for Scientists and Engineers," Princeton University Press, Twelfth Edition, 2008.
- [7] R. Dorf and R. Bishop, "Modern Control Systems," Prentice Hall, Twelfth Edition, 2011.
- [8] J. Lygeros and F. Ramponi, "Lecture Notes on Linear System Theory," ETH Zurich, pp. 1–158, 2013.